
Product data sheet



GF Instaflex adapter / flat seal 20x3/4"

1152582

- Socket fusion transition to lose-nut adapter
- Thread in DZR brass, UBA listed
- Gasket: EPDM
- Material: PB, Brass
- PN 16 at 20°C



About GF Instaflex adapter / flat seal

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification for environmental and process safety.
- The INSTAFLEX system meets all the essential requirements for building technology applications and is subject to constant monitoring by the licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes,
multi-family residfential buildings, healthcare, eduacation,
industrial, or commercial building


Application areas
- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex adapter / flat seal 20x3/4"

1152582



Measurements

Cylindric_thread_G	3/4"
LENGTH_L	102
Z Measurement d	20
Z Measurement L	102
Z	94

Product code

Item no EAN	7611205903534
Item no GF	761069685
Item no GTIN	07611205903534

Dimensions

Item Unit Height	16.5
Item Unit Length	111.186
Item Unit Weight	0,158
Item Unit Width	16.5
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900113465
Packaging Height PL1	40
Packaging Length PL1	140
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000224
Packaging Weight PL1	0,235
Packaging Width PL1	40

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+