
Product data sheet



GF Instaflex adapter MT 20x1/2"

1152609

- Socket fusion transition to male thread
- Thread in DZR brass, UBA listed
- Gasket: EPDM
- Material: PB, Brass



About GF Instaflex adapter MT

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification for environmental and process safety.
- The INSTAFLEX system meets all the essential requirements for building technology applications and is subject to constant monitoring by the licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes,
multi-family residfential buildings, healthcare, eduacation,
industrial, or commercial building


Application areas
- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex adapter MT 20x1/2"

1152609



Product code

Item no EAN	7611205903596
Item no GF	761069712
Item no GTIN	07611205903596

Dimensions

Item Unit Height	42
Item Unit Length	94
Item Unit Weight	0,12
Item Unit Width	41
Item_UOM	pce

Measurements

LENGTH_L	90
Male_thread_R	1/2
Z Measurement d	20
Z Measurement L	90
Z	37

Packaging

Packaging GTIN PL1	06414900113724
Packaging Height PL1	60
Packaging Length PL1	92
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,0003312
Packaging Weight PL1	0,13
Packaging Width PL1	60

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+