



GF Instaflex tee adapter 90deg MT d25

1152635

- Electro fusion T-piece with transition to male thread
- Thread in DZR brass, UBA listed (Umwelt Bundesamt, Germany)
- EPDM sealing hot and cold water



About GF Instaflex tee adapter 90deg MT

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification for environmental and process safety. The INSTAFLEX system meets all the essential requirements for building technology applications and is subject to constant monitoring by the licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas



- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex tee adapter 90deg MT d25

1152635



Product code

Item no EAN	7611205904340
Item no GF	761069738
Item no GTIN	07611205904340

Dimensions

Item Unit Height	117
Item Unit Length	46
Item Unit Weight	0,225
Item Unit Width	110
Item_UOM	pce

Measurements

Length (l2)	88
z1	16
Z2	73

Packaging

Packaging GTIN PL1	06414900113809
Packaging Height PL1	74
Packaging Length PL1	160
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,00150368
Packaging Weight PL1	0,231876555232505
Packaging Width PL1	127

Technical documents

Download documents here

enquiries.uk@uponor.com

www.uponor.com/en-gb