



GF Instaflex tee reduced 90° MT d32

1152636

- Electro fusion T-piece with transition to male thread
- Thread in DZR brass, UBA listed (Umwelt Bundesamt, Germany)
- EPDM sealing hot and cold water



About GF Instaflex tee reduced 90° MT

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification for environmental and process safety. The INSTAFLEX system meets all the essential requirements for building technology applications and is subject to constant monitoring by the licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas



- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex tee reduced 90° MT d32

1152636



Product code

Item no EAN	7611205904357
Item no GF	761069739
Item no GTIN	07611205904357

Dimensions

Item Unit Height	123
Item Unit Length	54
Item Unit Weight	0,246
Item Unit Width	120
Item_UOM	pce

Measurements

Length (l2)	97
Male_thread_R	1
Z Measurement d	32
Z Measurement L1	60
z1	18
Z2	80

Packaging

Packaging GTIN PL1	06414900113816
Packaging Height PL1	87
Packaging Length PL1	156
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,001940796
Packaging Weight PL1	0,272
Packaging Width PL1	143

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com