


GF Instaflex transition d25

1152670

- Material: V4A / 316L
- PN 16 at 20°C



About GF Instaflex transition

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification
- for environmental and process safety. The INSTAFLEX system meets all the essential
- requirements for building technology applications and is subject to constant monitoring by the
- licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas


- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex transition d25

1152670



Product code

Item no EAN	7611205910600
Item no GF	761069775
Item no GTIN	07611205910600

Dimensions

Item Unit Height	37
Item Unit Length	104
Item Unit Weight	0,143
Item Unit Width	37
Item_UOM	pce

Measurements

Length (l1)	43
Length (l2)	15

Packaging

Packaging GTIN PL1	06414900114097
Packaging Height PL1	37
Packaging Length PL1	104
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000142376
Packaging Weight PL1	0,145
Packaging Width PL1	37

Technical documents

[Download documents here](#)

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb