

GF Malleable Fittings long sweep bend 2 90deg 4 B

1152761

- Long sweep bend 90°, ISO/EN G1
- Female / female



About GF Malleable Fittings long sweep bend 2 90deg

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings long sweep bend 2 90deg 4 B

1152761



Status

Item Available From date 2025-09-05

Product code

Item no EAN	7611205300487
Item no GF	770002112
Item no GTIN	07611205300487
Item no RSK	1265420
Item no VVS	004002116

Dimensions

Item Unit Height	135
Item Unit Length	328
Item Unit Weight	8,38
Item Unit Width	328
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205100483
Packaging GTIN PL4	06414900242387
Packaging Height PL1	410
Packaging Height PL4	948
Packaging Length PL1	380
Packaging Length PL4	1200
Packaging Quantity PL1	2
Packaging Quantity PL4	36
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,039729
Packaging Volume PL4	0,91008
Packaging Weight PL1	17,3

Packaging Weight PL4	321,68
Packaging Width PL1	255
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb