

## GF Malleable Fittings long sweep bend 2 90deg 3/4 G

### 1152765

- Long sweep bend 90°, ISO/EN G1
- Female / female



## About GF Malleable Fittings long sweep bend 2 90deg

### Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

### Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

## GF Malleable Fittings long sweep bend 2 90deg 3/4 G

1152765



### Status

Item Available From date

2025-09-05

### Product code

Item no EAN	7611205400392
Item no GF	770002205
Item no GTIN	07611205400392
Item no LVI	0855009
Item no NOBB	60638822
Item no NRF	1366554
Item no RSK	1265495
Item no VVS	004002406

### Dimensions

Item Unit Height	38
Item Unit Length	88
Item Unit Weight	0,335
Item Unit Width	88
Item_UOM	pce

### Packaging

Packaging GTIN PL1	07611205200398
Packaging GTIN PL4	06414900069601
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	40
Packaging Quantity PL4	2160
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	13,614
Packaging Weight PL4	743,6
Packaging Width PL1	190
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)