


GF Malleable Fittings 3 - long sweep bend galvanized 90° 2

1152794

- Long sweep bend 90°, ISO/EN G8



About GF Malleable Fittings 3 - long sweep bend galvanized 90°

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 3 - long sweep bend galvanized 90° 2

1152794



Product code

Item no EAN	7611205400767
Item no GF	770003209
Item no GTIN	07611205400767
Item no RSK	1265834
Item no VVS	004003412

Dimensions

Item Unit Height	60
Item Unit Length	160
Item Unit Weight	1,2941
Item Unit Width	160
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205200763
Packaging GTIN PL4	06414900069342
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL4	270
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	6,6845
Packaging Weight PL4	369,407
Packaging Width PL1	190

Packaging Width PL4	800
---------------------	-----

Measurements

Z Measurement b	130
-----------------	-----

Z Measurement d	2
-----------------	---

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com