Product data sheet




GF Malleable Fittings 1A - short bend galvanized 90° 1/2

1152809

- Short bend 90°, ISO/EN D4





About GF Malleable Fittings 1A - short bend galvanized 90°

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 1A - short bend galvanized 90° 1/2

1152809





Product code

Item no EAN	7611205400224
Item no GF	770011204
Item no GTIN	07611205400224
Item no RSK	1267186
Item no VVS	004010404

Dimensions

Item Unit Height	32
Item Unit Length	56
Item Unit Weight	0,152
Item Unit Width	61
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205600228
Packaging GTIN PL2	07611205200220
Packaging GTIN PL4	06414900069724
Packaging Height PL1	32
Packaging Height PL2	200
Packaging Height PL4	729
Packaging Length PL1	225
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	80
Packaging Quantity PL4	4320
Packaging Type PL1	Plastic_Bag

Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,003816
Packaging Volume PL2	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	1,53
Packaging Weight PL2	12,34
Packaging Weight PL4	691,36
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Measurements

Z Measurement A	45
Z Measurement b	45
Z Measurement d	1/2
Z	32

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+