


GF Malleable Fittings 2A - short bend black 90° 1/4

1152818

- Short bend 90°, ISO/EN D1



About GF Malleable Fittings 2A - short bend black 90°

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 2A - short bend black 90° 1/4

1152818



Product code

Item no EAN	7611205300531
Item no GF	770012102
Item no GTIN	07611205300531
Item no RSK	1305976
Item no VVS	004020102

Dimensions

Item Unit Height	23
Item Unit Length	42
Item Unit Weight	0,061
Item Unit Width	42
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205100537
Packaging GTIN PL4	06414900242370
Packaging Height PL1	100
Packaging Height PL4	508
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	80
Packaging Quantity PL4	5760
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	5
Packaging Weight PL4	371,36
Packaging Width PL1	190

Packaging Width PL4	800
---------------------	-----

Measurements

Z Measurement a	30
-----------------	----

Z Measurement a	30
-----------------	----

Z Measurement d	1/4
-----------------	-----

Z	20
---	----

Technical documents

[Download documents here](#) 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com