


GF Malleable Fittings short bend 2A 90° 1 G

1152833

- Short bend 90°, ISO/EN D1
- Female / female



About GF Malleable Fittings short bend 2A 90°

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings short bend 2A 90° 1 G

1152833



Product code

Item no EAN	7611205400576
Item no GF	770012206
Item no GTIN	07611205400576
Item no RSK	1267509
Item no VVS	004020408

Dimensions

Item Unit Height	46
Item Unit Length	86
Item Unit Weight	0,398
Item Unit Width	86
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205200572
Packaging GTIN PL4	06414900069489
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	30
Packaging Quantity PL4	1620
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	12,154
Packaging Weight PL4	664,76
Packaging Width PL1	190

Packaging Width PL4

800

Measurements

Z 46

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb