

## GF Malleable Fittings long sweep bend 40 45° 2 G

**1152864**

- Long sweep bend 45°, ISO/EN G4/45°
- Male / female



### About GF Malleable Fittings long sweep bend 40 45°

#### Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

#### Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

## GF Malleable Fittings long sweep bend 40 45° 2 G

1152864



### Status

Item Available From date

2025-09-05

### Product code

Item no EAN	7611205404659
Item no GF	770040209
Item no GTIN	07611205404659
Item no LVI	0855020
Item no NOBB	60638844
Item no NRF	1366576
Item no RSK	1266238
Item no VVS	004040412

### Dimensions

Item Unit Height	62
Item Unit Length	112
Item Unit Weight	1,133
Item Unit Width	152
Item_UOM	pce

### Packaging

Packaging GTIN PL1	07611205204655
Packaging GTIN PL4	06414900242240
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	385
Packaging Length PL4	1200
Packaging Quantity PL1	15
Packaging Quantity PL4	405
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,019635
Packaging Volume PL4	0,69984
Packaging Weight PL1	17,415
Packaging Weight PL4	478,865
Packaging Width PL1	255
Packaging Width PL4	800

## Measurements

Z	57
---	----

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)