


## GF Malleable Fittings long sweep bend 41 45° 3/8 B

### 1152868

- Long sweep bend 45°, ISO/EN G1/45°
- Female / female



## About GF Malleable Fittings long sweep bend 41 45°

### Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

### Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

## GF Malleable Fittings long sweep bend 41 45° 3/8 B

1152868



### Status

Item Available From date 2025-09-05

### Product code

Item no EAN	7611205304775
Item no GF	770041103
Item no GTIN	07611205304775
Item no RSK	1266329
Item no VVS	004041103

### Dimensions

Item Unit Height	27
Item Unit Length	43
Item Unit Weight	0,1023
Item Unit Width	60
Item_UOM	pce

### Packaging

Packaging GTIN PL1	07611205104771
Packaging GTIN PL4	06414900184670
Packaging Height PL1	100
Packaging Height PL4	508
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	50
Packaging Quantity PL4	3600
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	5,235

Packaging Weight PL4	388,28
Packaging Width PL1	190
Packaging Width PL4	800

## Measurements

Z	20
---	----

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)