


GF Malleable Fittings long sweep bend 41 45deg 1 1/4 G

1152881

- Long sweep bend 45°, ISO/EN G1/45°
- Female / female



About GF Malleable Fittings long sweep bend 41 45deg

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings long sweep bend 41 45deg 1 1/4 G

1152881



Status

Item Available From date 2025-09-05

Product code

Item no EAN	7611205404819
Item no GF	770041207
Item no GTIN	07611205404819
Item no NOBB	60672591
Item no NRF	1387698
Item no RSK	1266519
Item no VVS	004041410

Dimensions

Item Unit Height	55
Item Unit Length	88
Item Unit Weight	0,607
Item Unit Width	127
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205204815
Packaging GTIN PL4	06414900242165
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	15
Packaging Quantity PL4	810
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988

Packaging Volume PL4	0,69984
Packaging Weight PL1	9,319
Packaging Weight PL4	511,67
Packaging Width PL1	190
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb