


GF Malleable Fittings bend 51 30° 3/4 G

1152903

- Bend 30°
- Female / female



About GF Malleable Fittings bend 51 30°

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings bend 51 30° 3/4 G

1152903



Product code

Item no EAN	7611205405656
Item no GF	770051205
Item no GTIN	07611205405656
Item no RSK	1306003
Item no VVS	004051406

Dimensions

Item Unit Height	38
Item Unit Length	49
Item Unit Weight	0,157
Item Unit Width	75
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205605650
Packaging GTIN PL2	07611205205652
Packaging GTIN PL4	06414900187497
Packaging Height PL1	38
Packaging Height PL2	200
Packaging Height PL4	729
Packaging Length PL1	225
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	50
Packaging Quantity PL4	2700
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,0045315
Packaging Volume PL2	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	1,58
Packaging Weight PL2	8
Packaging Weight PL4	457
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Measurements

Z 21

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb