

## GF Malleable Fittings 90 - elbow reducing, black 90° 3/4 - 1/2

1152962

- Elbow 90°, reducing, ISO/EN A1



### About GF Malleable Fittings 90 - elbow reducing, black 90°

#### Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

#### Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

## GF Malleable Fittings 90 - elbow reducing, black 90° 3/4 - 1/2

1152962



### Product code

Item no EAN	7611205307554
Item no GF	770090120
Item no GTIN	07611205307554
Item no LVI	0755027
Item no RSK	1270396
Item no VVS	004090133

### Dimensions

Item Unit Height	38
Item Unit Length	50
Item Unit Weight	0,149
Item Unit Width	46
Item_UOM	pce

### Packaging

Packaging GTIN PL1	07611205507558
Packaging GTIN PL2	07611205107550
Packaging GTIN PL4	06414900184281
Packaging Height PL1	38
Packaging Height PL2	200
Packaging Height PL4	729
Packaging Length PL1	225
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	80
Packaging Quantity PL4	4320
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,0045315
Packaging Volume PL2	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	1,5
Packaging Weight PL2	12,1
Packaging Weight PL4	678,4
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800
<b>Measurements</b>	
Z Measurement a	30
Z Measurement a	30
Z Measurement b	31
z1	15
Z2	18

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavillion  
 WD18 8GA, Watford  
 UK

T +44 (0)1923 381212  
 E  
 customerservice.uk.bfs@georgfi  
 scher.com