

GF Malleable Fittings elbow equal 92 90deg 2 1/2 B

1153028

- Elbow 90°, equal, ISO/EN A4
- Male / female



About GF Malleable Fittings elbow equal 92 90deg

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings elbow equal 92 90deg 2 1/2 B

1153028



Product code

Item no EAN	7611205308131
Item no GF	770092110
Item no GTIN	07611205308131
Item no NOBB	60638908
Item no NRF	1366640
Item no RSK	1271394
Item no VVS	004092113

Dimensions

Item Unit Height	92
Item Unit Length	107
Item Unit Weight	1,288
Item Unit Width	134
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205108137
Packaging GTIN PL4	06414900184069
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	385
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL4	270
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,019635
Packaging Volume PL4	0,69984
Packaging Weight PL1	13,3

Packaging Weight PL4	367,76
Packaging Width PL1	255
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb