

## GF Malleable Fittings elbow red 92 90deg 1 - 3/4 B

**1153033**

- Elbow 90°, female thread reduced, ISO/EN A4
- Male / female



### About GF Malleable Fittings elbow red 92 90deg

#### Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

#### Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

## GF Malleable Fittings elbow red 92 90deg 1 - 3/4 B

1153033



### Status

Item Available From date

2025-09-05

### Product code

Item no EAN	7611205308315
Item no GF	770092118
Item no GTIN	07611205308315
Item no RSK	1306062
Item no VVS	004092143

### Dimensions

Item Unit Height	46
Item Unit Length	52
Item Unit Weight	0,19
Item Unit Width	65
Item_UOM	pce

### Packaging

Packaging GTIN PL1	07611205508319
Packaging GTIN PL2	07611205108311
Packaging GTIN PL4	06414900183987
Packaging Height PL1	46
Packaging Height PL2	200
Packaging Height PL4	729
Packaging Length PL1	270
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	50
Packaging Quantity PL4	2700
Packaging Type PL1	Plastic_Bag

Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0065826
Packaging Volume PL2	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	1,91
Packaging Weight PL2	9,65
Packaging Weight PL4	546,1
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)