


GF Malleable Fittings elbow 94 90° 1/2 B

1153075

- Elbow 90°
- Male / male



About GF Malleable Fittings elbow 94 90°

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings elbow 94 90° 1/2 B

1153075



Product code

Item no EAN	7611205308636
Item no GF	770094104
Item no GTIN	07611205308636
Item no RSK	1306078
Item no VVS	004094104

Dimensions

Item Unit Height	22
Item Unit Length	48
Item Unit Weight	0,0899
Item Unit Width	48
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205508630
Packaging GTIN PL2	07611205108632
Packaging GTIN PL4	06414900183901
Packaging Height PL1	22
Packaging Height PL2	100
Packaging Height PL4	508
Packaging Length PL1	180
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	60
Packaging Quantity PL4	4320
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,0020988
Packaging Volume PL2	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	0,909
Packaging Weight PL2	5,554
Packaging Weight PL4	424,888
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb