


GF Malleable Fittings elbow 94 90deg 1 G

1153084

- Elbow 90°
- Male / male



About GF Malleable Fittings elbow 94 90deg

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings elbow 94 90deg 1 G

1153084



Product code

Item no EAN	7611205408657
Item no GF	770094206
Item no GTIN	07611205408657
Item no RSK	1306084
Item no VVS	004094408

Dimensions

Item Unit Height	34
Item Unit Length	64
Item Unit Weight	0,199
Item Unit Width	64
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205608651
Packaging GTIN PL2	07611205208653
Packaging GTIN PL4	06414900186629
Packaging Height PL1	34
Packaging Height PL2	100
Packaging Height PL4	508
Packaging Length PL1	270
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	20
Packaging Quantity PL4	1440
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet

Packaging Volume PL1	0,0048654
Packaging Volume PL2	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	2
Packaging Weight PL2	4,1
Packaging Weight PL4	320,2
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb