Product data sheet




GF Malleable Fittings 95 - union elbow, flat seat, galvanized 1

1153102

- Union elbow, flat seat, ISO/EN UA1

- Supplied without sealing gaskets; a and z2 include the seal thickness as per table "Sealing Gasket Dimension".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
- * Inside hexagon





About GF Malleable Fittings 95 - union elbow, flat seat, galvanized

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 95 - union elbow, flat seat, galvanized 1

1153102





Status

Item Available From date	2025-09-05

Product code

Item no EAN	7611205409050
Item no GF	770095206
Item no GTIN	07611205409050
Item no RSK	1261206
Item no VVS	004095408

Dimensions

Item Unit Height	55
Item Unit Length	79
Item Unit Weight	0,526
Item Unit Width	95
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205209056
Packaging GTIN PL4	06414900186490
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	25
Packaging Quantity PL4	1350
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988

Packaging Volume PL4	0,69984
Packaging Weight PL1	13,364
Packaging Weight PL4	730,1
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Wall thickness_s1	38
Wall thickness_s2	55
Z Measurement A	72
Z Measurement d	1
z1	21
Z2	55

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+