# Product data sheet




# GF Malleable Fittings 95 - union elbow, flat seat, galvanized 1 1/4

## 1153103

- Union elbow, flat seat, ISO/EN UA1

- Supplied without sealing gaskets; a and z2 include the seal thickness as per table "Sealing Gasket Dimension".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
- * Inside hexagon




## About GF Malleable Fittings 95 - union elbow, flat seat, galvanized

### Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


### Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

# GF Malleable Fittings 95 - union elbow, flat seat, galvanized 1 1/4

## 1153103




### Status

| | |
|---|---|
| Item Available From date | 2025-09-05 |

### Product code

| | |
|---|---|
| Item no EAN | 7611205409074 |
| Item no GF | 770095207 |
| Item no GTIN | 07611205409074 |
| Item no RSK | 1261208 |
| Item no VVS | 004095410 |

### Dimensions

| | |
|---|---|
| Item Unit Height | 67 |
| Item Unit Length | 86 |
| Item Unit Weight | 0,829 |
| Item Unit Width | 110 |
| Item_UOM | pce |

### Packaging

| | |
|---|---|
| Packaging GTIN PL1 | 07611205209070 |
| Packaging GTIN PL4 | 06414900186483 |
| Packaging Height PL1 | 200 |
| Packaging Height PL4 | 729 |
| Packaging Length PL1 | 260 |
| Packaging Length PL4 | 1200 |
| Packaging Quantity PL1 | 12 |
| Packaging Quantity PL4 | 648 |
| Packaging Type PL1 | Base_Box |
| Packaging Type PL4 | Pallet |
| Packaging Volume PL1 | 0,00988 |

| | |
|---|---|
| Packaging Volume PL4 | 0,69984 |
| Packaging Weight PL1 | 10,162 |
| Packaging Weight PL4 | 557,192 |
| Packaging Width PL1 | 190 |
| Packaging Width PL4 | 800 |

## Measurements

| | |
|---|---|
| Wall thickness_s1 | 48 |
| Wall thickness_s2 | 67 |
| Z Measurement A | 82 |
| Z Measurement d | 1 1/4 |
| z1 | 26 |
| Z2 | 63 |

## Technical documents

Download documents here

# Excellence in Flow

Visit our webpage to get in contact with your local specialist:
**www.georgfischer.com/locations**



**Uponor UK**

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+