Product data sheet




GF Malleable Fittings 96 - union elbow, taper seat, galvanized 1 1/4

1153121

- Union elbow, taper seat, ISO/EN UA11
- Torque and notes for installation please find in "Technical Product Notes".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
- * Inside hexagon





About GF Malleable Fittings 96 - union elbow, taper seat, galvanized

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 96 - union elbow, taper seat, galvanized 1 1/4

1153121





Status

Item Available From date	2025-09-05

Product code

Item no EAN	7611205409562
Item no GF	770096207
Item no GTIN	07611205409562
Item no RSK	1262617
Item no VVS	004096410

Dimensions

Item Unit Height	67
Item Unit Length	82
Item Unit Weight	0,897
Item Unit Width	110
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205209568
Packaging GTIN PL4	06414900186353
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	12
Packaging Quantity PL4	648
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988

Packaging Volume PL4	0,69984
Packaging Weight PL1	10,978
Packaging Weight PL4	601,256
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Wall thickness_s1	48
Wall thickness_s2	67
Z Measurement A	82
Z Measurement d	1 1/4
z1	26
Z2	63

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+