Product data sheet




GF Malleable Fittings 120 - elbow galvanized 45° 3/4

1153196

- Elbow 45°, ISO/EN A1/45°





About GF Malleable Fittings elbow 45°

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 120 - elbow galvanized 45° 3/4

1153196





Product code

Item no EAN	7611205412623
Item no GF	770120205
Item no GTIN	07611205412623
Item no NOBB	60638913
Item no NRF	1366645
Item no RSK	1306096
Item no VVS	004120406

Dimensions

Item Unit Height	38
Item Unit Length	47
Item Unit Weight	0,119
Item Unit Width	54
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205612627
Packaging GTIN PL2	07611205212629
Packaging GTIN PL4	06414900185554
Packaging Height PL1	38
Packaging Height PL2	100
Packaging Height PL4	508
Packaging Length PL1	180
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	40

Packaging Quantity PL4	2880
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0036252
Packaging Volume PL2	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	1,195
Packaging Weight PL2	4,88
Packaging Weight PL4	376,36
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Measurements

Z Measurement A	25
Z Measurement d	3/4
Z	10

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+