Product data sheet




GF Malleable Fittings elbow 45° 1

1153212

- Malleable cast iron
- Elbow 45°
- ISO/EN A4/45°





About GF Malleable Fittings 121 - elbow black 45°

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings elbow 45° 1

1153212





Product code

Item no EAN	7611205312794
Item no GF	770121106
Item no GTIN	07611205312794
Item no NOBB	60638926
Item no NRF	1366658
Item no RSK	1306115
Item no VVS	004121108

Dimensions

Item Unit Height	46
Item Unit Length	52
Item Unit Weight	0,213
Item Unit Width	74
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205512798
Packaging GTIN PL2	07611205112790
Packaging GTIN PL4	06414900182737
Packaging Height PL1	46
Packaging Height PL2	200
Packaging Height PL4	729
Packaging Length PL1	225
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	50

Packaging Quantity PL4	2700
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0054855
Packaging Volume PL2	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	2,14
Packaging Weight PL2	10,8
Packaging Weight PL4	608,2
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Measurements

Z Measurement A	28
Z Measurement b	39
Z Measurement d	1
Z	11

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+