


GF Malleable Fittings elbow 121 45° 2 B

1153215

- Elbow 45°, ISO/EN A1/45°
- Male / female



About GF Malleable Fittings elbow 121 45°

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings elbow 121 45° 2 B

1153215



Product code

Item no EAN	7611205312824
Item no GF	770121109
Item no GTIN	07611205312824
Item no NOBB	60638932
Item no NRF	1366664
Item no RSK	1306122
Item no VVS	004121112

Dimensions

Item Unit Height	75
Item Unit Length	84
Item Unit Weight	0,66
Item Unit Width	109
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205112820
Packaging GTIN PL4	06414900182706
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	12
Packaging Quantity PL4	648
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	8,134

Packaging Weight PL4	447,68
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Z	19
---	----

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb