

GF Malleable Fittings tee reduced 130 2 1/2 - 1 1/2 B

1153234

- Malleable cast iron
- Tee, reducing or increasing on the branch, reducing on the run
- ISO/EN B1



About GF Malleable Fittings tee reduced 130

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee reduced 130 2 1/2 - 1 1/2 B

1153234



Product code

Item no EAN	7611205315252
Item no GF	770129118
Item no GTIN	07611205315252
Item no RSK	1280071
Item no VVS	004130173

Dimensions

Item Unit Height	92
Item Unit Length	109
Item Unit Weight	1,298
Item Unit Width	110
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205115258
Packaging GTIN PL4	06414900181686
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	385
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL4	270
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,019635
Packaging Volume PL4	0,69984
Packaging Weight PL1	13,4
Packaging Weight PL4	370,46
Packaging Width PL1	255

Packaging Width PL4

800

Measurements

z1

28

Z2

44

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb