

GF Malleable Fittings tee reducer 130 3 - 1 1/4 B

1153242

- Malleable cast iron
- Tee, reducing or increasing on the branch, reducing on the run
- ISO/EN B1



About GF Malleable Fittings tee reducer 130

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee reducer 130 3 - 1 1/4 B

1153242



Product code

| | |
|--------------|----------------|
| Item no EAN | 7611205315436 |
| Item no GF | 770129127 |
| Item no GTIN | 07611205315436 |
| Item no RSK | 1280081 |

Dimensions

| | |
|------------------|------|
| Item Unit Height | 107 |
| Item Unit Length | 124 |
| Item Unit Weight | 1,44 |
| Item Unit Width | 110 |
| Item_UOM | pce |

Packaging

| | |
|------------------------|----------------|
| Packaging GTIN PL1 | 07611205115432 |
| Packaging GTIN PL4 | 06414900181600 |
| Packaging Height PL1 | 200 |
| Packaging Height PL4 | 729 |
| Packaging Length PL1 | 385 |
| Packaging Length PL4 | 1200 |
| Packaging Quantity PL1 | 10 |
| Packaging Quantity PL4 | 270 |
| Packaging Type PL1 | Base_Box |
| Packaging Type PL4 | Pallet |
| Packaging Volume PL1 | 0,019635 |
| Packaging Volume PL4 | 0,69984 |
| Packaging Weight PL1 | 14,82 |
| Packaging Weight PL4 | 408,8 |
| Packaging Width PL1 | 255 |
| Packaging Width PL4 | 800 |

Measurements

| | |
|----|----|
| z1 | 25 |
| Z2 | 51 |

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb