

GF Malleable Fittings tee reduced 130 4 - 1 B

1153246

- Malleable cast iron
- Tee, reducing or increasing on the branch, reducing on the run
- ISO/EN B1



About GF Malleable Fittings tee reduced 130

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee reduced 130 4 - 1 B

1153246



Status

Item Available From date

2025-09-05

Product code

Item no EAN

7611205315634

Item no GF

770129133

Item no GTIN

07611205315634

Item no RSK

1280087

Dimensions

Item Unit Height

135

Item Unit Length

148

Item Unit Weight

2,29

Item Unit Width

112

Item_UOM

pce

Packaging

Packaging GTIN PL1

07611205115630

Packaging GTIN PL4

06414900181563

Packaging Height PL1

200

Packaging Height PL4

729

Packaging Length PL1

385

Packaging Length PL4

1200

Packaging Quantity PL1

6

Packaging Quantity PL4

162

Packaging Type PL1

Base_Box

Packaging Type PL4

Pallet

Packaging Volume PL1

0,019635

Packaging Volume PL4

0,69984

Packaging Weight PL1

14,16

Packaging Weight PL4

390,98

Packaging Width PL1	255
---------------------	-----

Packaging Width PL4	800
---------------------	-----

Measurements

z1	20
----	----

Z2	63
----	----

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb