

## GF Malleable Fittings tee reducer 130 3 - 2 - 2 G

**1153263**

- Malleable cast iron
- Tee, reducing or increasing on the branch, reducing on the run
- ISO/EN B1



### About GF Malleable Fittings tee reducer 130

#### Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

#### Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

## GF Malleable Fittings tee reducer 130 3 - 2 - 2 G

1153263



### Status

Item Available From date

2025-09-05

### Product code

Item no EAN	7611205415464
Item no GF	770129229
Item no GTIN	07611205415464
Item no RSK	1280048
Item no VVS	004130683

### Dimensions

Item Unit Height	107
Item Unit Length	127
Item Unit Weight	1,48
Item Unit Width	124
Item_UOM	pce

### Packaging

Packaging GTIN PL1	07611205215460
Packaging GTIN PL4	06414900126632
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	385
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL4	270
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,019635
Packaging Volume PL4	0,69984
Packaging Weight PL1	15,22

Packaging Weight PL4	419,6
Packaging Width PL1	255
Packaging Width PL4	800

## Measurements

z1	34
Z2	49
Z3	36

## Technical documents

[Download documents here](#) 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)