
Product data sheet



GF Malleable Fittings tee reduced 3/4 - 3/8

1153293

- Tee, reducing or increasing on the branch, reducing on the run, ISO/EN 81



About GF Malleable Fittings tee reduced

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee reduced 3/4 - 3/8

1153293



Product code

Item no EAN	7611205313494
Item no GF	770130124
Item no GTIN	07611205313494
Item no LVI	0755057
Item no RSK	1276518
Item no VVS	004130132

Dimensions

Item Unit Height	38
Item Unit Length	44
Item Unit Weight	0,205
Item Unit Width	56
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205513498
Packaging GTIN PL2	07611205113490
Packaging GTIN PL4	06414900182454
Packaging Height PL1	38
Packaging Height PL2	200
Packaging Height PL4	729
Packaging Length PL1	225
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	60
Packaging Quantity PL4	3240

Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0045315
Packaging Volume PL2	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	2,06
Packaging Weight PL2	12,46
Packaging Weight PL4	697,84
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Measurements

Z Measurement A	28
Z Measurement b	28
z1	13
Z2	18
Z3	13

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+