


GF Malleable Fittings tee reducer 130 3/4 - 1/2 - 1/2 B

1153295

- Tee, reducing or increasing on the branch, reducing on the run, ISO/EN 81
- Female /female /female



About GF Malleable Fittings tee reducer 130

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee reducer 130 3/4 - 1/2 - 1/2 B

1153295



Product code

Item no EAN	7611205313524
Item no GF	770130126
Item no GTIN	07611205313524
Item no LVI	0755060
Item no RSK	1280247
Item no VVS	004130237

Dimensions

Item Unit Height	38
Item Unit Length	50
Item Unit Weight	0,208
Item Unit Width	58
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205513528
Packaging GTIN PL2	07611205113520
Packaging GTIN PL4	06414900182430
Packaging Height PL1	38
Packaging Height PL2	200
Packaging Height PL4	729
Packaging Length PL1	225
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	60
Packaging Quantity PL4	3240
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,0045315
Packaging Volume PL2	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	2,09
Packaging Weight PL2	12,64
Packaging Weight PL4	707,56
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Measurements

z1	15
Z2	18
Z3	15

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb