

GF Malleable Fittings tee reducer 130 2 - 1/2 B

1153349

- Malleable cast iron
- Tee, reducing or increasing on the branch, reducing on the run
- ISO/EN B1



About GF Malleable Fittings tee reducer 130

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee reducer 130 2 - 1/2 B

1153349



Product code

Item no EAN	7611205314668
Item no GF	770130181
Item no GTIN	07611205314668
Item no LVI	0755090
Item no NOBB	60638978
Item no NRF	1366710
Item no RSK	1276880
Item no VVS	004130163

Dimensions

Item Unit Height	75
Item Unit Length	86
Item Unit Weight	0,693
Item Unit Width	76
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205114664
Packaging GTIN PL4	06414900181884
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	12
Packaging Quantity PL4	648
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984

Packaging Weight PL1	8,53
Packaging Weight PL4	469,064
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

z1	14
Z2	35

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb