


GF Malleable Fittings tee equal 130 2 1/2 G

1153376

- Tee, equal, ISO/EN B1
- Female /female /female



About GF Malleable Fittings tee equal 130

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee equal 130 2 1/2 G

1153376



Product code

Item no EAN	7611205413125
Item no GF	770130210
Item no GTIN	07611205413125
Item no LVI	0855091
Item no NOBB	60638988
Item no NRF	1366720
Item no RSK	1276245
Item no VVS	004130413

Dimensions

Item Unit Height	92
Item Unit Length	115
Item Unit Weight	1,839
Item Unit Width	138
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205213121
Packaging GTIN PL4	06414900185301
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	385
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL4	270
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,019635
Packaging Volume PL4	0,69984

Packaging Weight PL1	18,81
Packaging Weight PL4	516,53
Packaging Width PL1	255
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb