

GF Malleable Fittings tee reducer 130 1 - 3/4 - 3/4 G

1153403

- Malleable cast iron
- Tee, reducing or increasing on the branch, reducing on the run
- ISO/EN B1



About GF Malleable Fittings tee reducer 130

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee reducer 130 1 - 3/4 - 3/4 G

1153403



Status

Item Available From date

2025-09-05

Product code

Item no EAN	7611205413767
Item no GF	770130239
Item no GTIN	07611205413767
Item no LVI	0855065
Item no RSK	1283282
Item no VVS	004130566

Dimensions

Item Unit Height	46
Item Unit Length	59
Item Unit Weight	0,3
Item Unit Width	68
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205213763
Packaging GTIN PL4	06414900185035
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	30
Packaging Quantity PL4	1620
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984

Packaging Weight PL1	9,214
Packaging Weight PL4	506
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

z1	18
Z2	21
Z3	18

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb