

GF Malleable Fittings tee reducer 130 1 1/2 - 1 1/2 - 1/2 G

1153436

- Malleable cast iron
- Tee, reducing or increasing on the branch, reducing on the run
- ISO/EN B1



About GF Malleable Fittings tee reducer 130

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee reducer 130 1 1/2 - 1 1/2 - 1/2 G

1153436



Status

Item Available From date

2025-09-05

Product code

Item no EAN

7611205414481

Item no GF

770130273

Item no GTIN

07611205414481

Item no RSK

1280033

Item no VVS

004130628

Dimensions

Item Unit Height

62

Item Unit Length

81

Item Unit Weight

0,585

Item Unit Width

92

Item_UOM

pce

Packaging

Packaging GTIN PL1

07611205214487

Packaging GTIN PL4

06414900127028

Packaging Height PL1

200

Packaging Height PL4

729

Packaging Length PL1

260

Packaging Length PL4

1200

Packaging Quantity PL1

15

Packaging Quantity PL4

810

Packaging Type PL1

Base_Box

Packaging Type PL4

Pallet

Packaging Volume PL1

0,00988

Packaging Volume PL4

0,69984

Packaging Weight PL1

8,989

Packaging Weight PL4	493,85
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

z1	31
Z2	31
Z3	29

Technical documents

[Download documents here](#) 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb