

GF Malleable Fittings tee reduced 130 2 - 3/4 G

1153446

- Malleable cast iron
- Tee, reducing or increasing on the branch, reducing on the run
- ISO/EN B1



About GF Malleable Fittings tee reduced 130

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee reduced 130 2 - 3/4 G

1153446



Product code

Item no EAN	7611205414702
Item no GF	770130283
Item no GTIN	07611205414702
Item no LVI	0855087
Item no NOBB	60638980
Item no NRF	1366712
Item no RSK	1278191
Item no VVS	004130464

Dimensions

Item Unit Height	75
Item Unit Length	88
Item Unit Weight	0,726
Item Unit Width	80
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205214708
Packaging GTIN PL4	06414900126922
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	385
Packaging Length PL4	1200
Packaging Quantity PL1	25
Packaging Quantity PL4	675
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,019635
Packaging Volume PL4	0,69984

Packaging Weight PL1	18,57
Packaging Weight PL4	510,05
Packaging Width PL1	255
Packaging Width PL4	800

Measurements

z1	16
Z2	35

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb