

GF Malleable Fittings tee reducer 130 2 - 2 - 1 1/2 G

1153458

- Malleable cast iron
- Tee, reducing or increasing on the branch, reducing on the run
- ISO/EN B1



About GF Malleable Fittings tee reducer 130

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings tee reducer 130 2 - 2 - 1 1/2 G

1153458



Status

Item Available From date

2025-08-19

Product code

Item no EAN	7611205414924
Item no GF	770130296
Item no GTIN	07611205414924
Item no RSK	1284553
Item no VVS	004130662

Dimensions

Item Unit Height	75
Item Unit Length	96
Item Unit Weight	0,81
Item Unit Width	113
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205214920
Packaging GTIN PL4	06414900126809
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	8
Packaging Quantity PL4	432
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	8,2588

Packaging Weight PL4	369,92
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

z1	34
Z2	34
Z3	36

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb