


GF Malleable Fittings 131 - pitcher tee, reduced, black 1 1/4

1153502

- Pitcher tee, equal, ISO/EN E1



About GF Malleable Fittings 131 - pitcher tee, reduced, black

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 131 - pitcher tee, reduced, black 1 1/4

1153502



Product code

Item no EAN	7611205315900
Item no GF	770131107
Item no GTIN	07611205315900
Item no NOBB	60638994
Item no NRF	1366726
Item no RSK	1285766
Item no VVS	004131110

Dimensions

Item Unit Height	55
Item Unit Length	104
Item Unit Weight	0,778
Item Unit Width	116
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205115906
Packaging GTIN PL4	06414900181495
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL4	540
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	7,994

Packaging Weight PL4	440,12
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Z Measurement a	76
Z Measurement a	76
Z Measurement d	1 1/4
Z	57
Z3	21

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com