## GF Malleable Fittings pitcher tee reduced 131 3/4 - 3/4 - 1/2 B

1153510

- Pitcher tee, reducing on the branch, ISO/EN E1
- Swept tee to improve flow, especially on return lines

## About GF Malleable Fittings pitcher tee reduced 131

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings pitcher tee reduced 131 3/4 - 3/4 - 1/2 B

1153510

Product code

Item no EAN	7611205316112
Item no GF	770131117
Item no GTIN	07611205316112
Item no RSK	1287119
Item no VVS	004131241

Dimensions

Item Unit Height	38
Item Unit Length	68
Item Unit Weight	0,308
Item Unit Width	76
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205116118
Packaging GTIN PL4	06414900181419
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	30
Packaging Quantity PL4	1620
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	9,454
Packaging Weight PL4	518,96
Packaging Width PL1	190

Packaging Width PL4	800

Technical documents

Download documents here ⬇