


GF Malleable Fittings cross equal 180 1/4 B

1153620

- Cross, equal, ISO/EN C1
- Female/ female/ female/ female



About GF Malleable Fittings cross equal 180

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings cross equal 180 1/4 B

1153620



Status

Item Available From date

2025-09-05

Product code

Item no EAN	7611205321819
Item no GF	770180102
Item no GTIN	07611205321819
Item no RSK	1280203
Item no VVS	004180102

Dimensions

Item Unit Height	23
Item Unit Length	42
Item Unit Weight	0,1003
Item Unit Width	42
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205121815
Packaging GTIN PL4	06414900123211
Packaging Height PL1	100
Packaging Height PL4	508
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	60
Packaging Quantity PL4	4320
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	6,138

Packaging Weight PL4	453,296
Packaging Width PL1	190
Packaging Width PL4	800

Technical documents

[Download documents here](#) 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb