


## GF Malleable Fittings cross equal 180 2 1/2 B

**1153628**

- Cross, equal, ISO/EN C1
- Feamle/ female/ female/ female



### About GF Malleable Fittings cross equal 180

#### Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

#### Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

## GF Malleable Fittings cross equal 180 2 1/2 B

1153628



### Product code

Item no EAN	7611205321918
Item no GF	770180110
Item no GTIN	07611205321918
Item no RSK	1280220
Item no VVS	004180113

### Dimensions

Item Unit Height	92
Item Unit Length	138
Item Unit Weight	2,06
Item Unit Width	138
Item_UOM	pce

### Packaging

Packaging GTIN PL1	07611205121914
Packaging GTIN PL4	06414900123136
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	3
Packaging Quantity PL4	162
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	6,394
Packaging Weight PL4	353,72
Packaging Width PL1	190

Packaging Width PL4

800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)