Product data sheet




GF Malleable Fittings 180 - cross, equal, galvanized 1 1/4

1153642

- Cross, equal, ISO/EN C1





About GF Malleable Fittings 180 - cross, equal, galvanized

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 180 - cross, equal, galvanized 1 1/4

1153642





Product code

Item no EAN	7611205421861
Item no GF	770180207
Item no GTIN	07611205421861
Item no LVI	0855101
Item no RSK	1300219
Item no VVS	004180410

Dimensions

Item Unit Height	55
Item Unit Length	90
Item Unit Weight	0,69
Item Unit Width	90
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205221867
Packaging GTIN PL4	06414900125857
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	15
Packaging Quantity PL4	810
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984

Packaging Weight PL1	10,564
Packaging Weight PL4	578,9
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Z Measurement A	45
Z Measurement d	1 1/4
Z	26

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+