
Product data sheet



GF Malleable Fittings 240 - socket, reduced, black 1/4 - 1/8 STA

1153682

- Socket, reducing, ISO/EN M2



About GF Malleable Fittings 240 - socket, reduced, black

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 240 - socket, reduced, black 1/4 - 1/8 STA

1153682



Product code

Item no EAN	7611205324292
Item no GF	770240115
Item no GTIN	07611205324292
Item no RSK	1313204
Item no VVS	004240120

Dimensions

Item Unit Height	23
Item Unit Length	23
Item Unit Weight	0,023
Item Unit Width	27
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205524296
Packaging GTIN PL2	07611205124298
Packaging GTIN PL4	06414900122900
Packaging Height PL1	23
Packaging Height PL2	100
Packaging Height PL4	508
Packaging Length PL1	135
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	100
Packaging Quantity PL4	7200
Packaging Type PL1	Plastic_Bag

Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00164565
Packaging Volume PL2	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	0,235
Packaging Weight PL2	2,467
Packaging Weight PL4	202,593
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Measurements

Wall thickness_s	17
Z Measurement A	27
Z Measurement A	27
Z2	10

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+