

GF Malleable Fittings socket reduced 240 3 - 1 1/2 B

1153709

- 'ST' - these types of fittings are made from steel (galvanised finish = electroplated)
- Not suitable for drinking water installations.
- Steel parts are hexagonal instead of beaded at the end no. 1.



About GF Malleable Fittings socket reduced 240

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings socket reduced 240 3 - 1 1/2 B

1153709



Product code

| | |
|--------------|----------------|
| Item no EAN | 7611205324889 |
| Item no GF | 770240143 |
| Item no GTIN | 07611205324889 |
| Item no RSK | 1363665 |
| Item no VVS | 004240179 |

Dimensions

| | |
|------------------|-------|
| Item Unit Height | 107 |
| Item Unit Length | 107 |
| Item Unit Weight | 0,922 |
| Item Unit Width | 80 |
| Item_UOM | pce |

Packaging

| | |
|------------------------|----------------|
| Packaging GTIN PL1 | 07611205124885 |
| Packaging GTIN PL4 | 06414900122634 |
| Packaging Height PL1 | 200 |
| Packaging Height PL4 | 729 |
| Packaging Length PL1 | 385 |
| Packaging Length PL4 | 1200 |
| Packaging Quantity PL1 | 20 |
| Packaging Quantity PL4 | 540 |
| Packaging Type PL1 | Base_Box |
| Packaging Type PL4 | Pallet |
| Packaging Volume PL1 | 0,019635 |
| Packaging Volume PL4 | 0,69984 |
| Packaging Weight PL1 | 18,86 |
| Packaging Weight PL4 | 517,88 |
| Packaging Width PL1 | 255 |

Packaging Width PL4

800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb