Product data sheet




GF Malleable Fittings 241 - reducing bush, black 4 - 2

1153796

- Reducing bush, ISO/EN N4

- Forms I, II, III are available only as marked under column "Form", Form I can also be supplied
- with continuous internal thread (=241D).
- ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not
- suitable for drinking water installations.





About GF Malleable Fittings 241 - reducing bush, black

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"


Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 241 - reducing bush, black 4 - 2

1153796





Product code

Item no EAN	7611205325909
Item no GF	770241151
Item no GTIN	07611205325909
Item no RSK	1318145
Item no VVS	004241191

Dimensions

Item Unit Height	120
Item Unit Length	138
Item Unit Weight	1,591
Item Unit Width	69
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205125905
Packaging GTIN PL4	06414900122207
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	6
Packaging Quantity PL4	324
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	9,76

Packaging Weight PL4	535,484
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Z Measurement A	51
Z Measurement b	69
Z MEASUREMENT S	120
Z	45

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+