


GF Malleable Fittings 241 - reducing bush, galvanized 3 - 1

1153830

- Reducing bush, ISO/EN N4
- Forms I, II, III are available only as marked under column "Form", Form I can also be supplied
- with continuous internal thread (=241D).
- ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not
- suitable for drinking water installations.



About GF Malleable Fittings 241 - reducing bush, galvanized

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 241 - reducing bush, galvanized 3 - 1

1153830



Product code

Item no EAN	7611205425739
Item no GF	770241246
Item no GTIN	07611205425739
Item no RSK	1319581
Item no VVS	004241477

Dimensions

Item Unit Height	95
Item Unit Length	109
Item Unit Weight	0,968
Item Unit Width	59
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205225735
Packaging GTIN PL4	06414900124942
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL4	540
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	9,894
Packaging Weight PL4	542,72
Packaging Width PL1	190

Packaging Width PL4	800
Measurements	
Wall thickness_s	95
Z Measurement a	44
Z Measurement a	44
Z Measurement b	59
Z MEASUREMENT S	95
Z	42

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com