


GF Malleable Fittings 245 - hexagonal nipple, reduced, galvanized 1 1/4 - 3/4

1153900

- Hexagon nipple, reducing, ISO/EN N8
- ST ... these types of fittings are made from steel (galvanised finish = electroplated)
- and not suitable for drinking water installations.



About GF Malleable Fittings 245 - hexagonal nipple, reduced, galvanized

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 245 - hexagonal nipple, reduced, galvanized 1 1/4 - 3/4

1153900



Product code

Item no EAN	7611205426385
Item no GF	7702452226
Item no GTIN	07611205426385
Item no LVI	0855154
Item no NOBB	60639103
Item no NRF	1366835
Item no RSK	1317692
Item no VVS	004245450

Dimensions

Item Unit Height	46
Item Unit Length	53
Item Unit Weight	0,235
Item Unit Width	57
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205226381
Packaging GTIN PL4	06414900124751
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	60
Packaging Quantity PL4	3240
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988

Packaging Volume PL4	0,69984
Packaging Weight PL1	14,314
Packaging Weight PL4	781,4
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Wall thickness_s	46
Z Measurement a	57
Z Measurement a	57
Z MEASUREMENT S	46

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com