
Product data sheet



GF Malleable Fittings 246 - socket reduced, black 2 - 1 1/4

1153938

- Socket, reducing, ISO/EN M4
- ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not
- suitable for drinking water installations. Steel parts are hexagonal instead of
- beaded at the end no. 1.



About GF Malleable Fittings 246 - socket reduced, black

Specification


- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5
to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT)
acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment
Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees,
between 120-300 degrees use interpolated values,
Max. 20bar at 300 degrees
- Sizes from ¼" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings 246 - socket reduced, black 2 - 1 1/4

1153938



Product code

Item no EAN	7611205326913
Item no GF	770246130
Item no GTIN	07611205326913
Item no RSK	1363691
Item no VVS	004246166

Dimensions

Item Unit Height	75
Item Unit Length	75
Item Unit Weight	0,437
Item Unit Width	70
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205126919
Packaging GTIN PL4	06414900121774
Packaging Height PL1	200
Packaging Height PL4	729
Packaging Length PL1	260
Packaging Length PL4	1200
Packaging Quantity PL1	20
Packaging Quantity PL4	1080
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00988
Packaging Volume PL4	0,69984
Packaging Weight PL1	8,954

Packaging Weight PL4	491,96
Packaging Width PL1	190
Packaging Width PL4	800

Measurements

Z Measurement A	70
Z	46

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+