

GF Malleable Fittings socket reduced 246 1/2 - 3/8 G

1153947

- Socket, reducing, ISO/EN M4
- 'ST' these types of fittings are made from steel (galvanised finish = electroplated)
- Not suitable for drinking water installations
- Steel parts are hexagonal instead of beaded at the end no. 1.



About GF Malleable Fittings socket reduced 246

Specification

- Unique Whiteheart ductile Cast Iron to EN-GJMW-400-5 to BS EN 1562, design symbol A
- Thread type BSP - R or Rp to BS EN 10226-1 / ISO 7-1
- Union or flat-nut thread types to BS EN 228-1
- Manufactured to BS EN 10242 (ISO 49)
- Cast Iron is fire class A1 to BS EN 13501-1 (CWFT) acc. to Commission Decision 96/603/EC (as amended)
- Natural Black or Galvanized (99.995 zinc)
- Coated with medical-grade oil for corrosion protection
- Suitable for systems covered by the Pressure Equipment Safety Regulation:2016
- Max. pressure 25 bar up to 120 degrees, between 120-300 degrees use interpolated values, Max. 20bar at 300 degrees
- Sizes from 1/4" to 4"

Application

- Heating - LTHW, MTHW and HTHW
- Steam
- Chilled water and cooling applications
- Compressed air
- Fuel gases
- Fuel oils
- Fire defence / sprinklers

GF Malleable Fittings socket reduced 246 1/2 - 3/8 G

1153947



Status

Item Available From date

2025-09-05

Product code

Item no EAN	7611205426712
Item no GF	770246218
Item no GTIN	07611205426712
Item no RSK	1363679
Item no VVS	004246426

Dimensions

Item Unit Height	32
Item Unit Length	32
Item Unit Weight	0,088
Item Unit Width	43
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205626716
Packaging GTIN PL2	07611205226718
Packaging GTIN PL4	06414900124591
Packaging Height PL1	32
Packaging Height PL2	100
Packaging Height PL4	508
Packaging Length PL1	155
Packaging Length PL2	260
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	80
Packaging Quantity PL4	5760
Packaging Type PL1	Plastic_Bag

Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0026288
Packaging Volume PL2	0,00494
Packaging Volume PL4	0,48768
Packaging Weight PL1	0,89
Packaging Weight PL2	7,22
Packaging Weight PL4	544,84
Packaging Width PL1	530
Packaging Width PL2	190
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb